

## 4MP WDR IP DOME CAMERA

### OE-C7624-AWR REVB



#### DESCRIPTION


The OE-C7624-AWR REVB is an IP dome camera, with a maximum resolution of 4MP. This camera uses True WDR to improve recording quality in high and low light. The OE-C7624-AWR REVB comes with a motorized 2.7-12mm digital zoom lens, with autofocus to speed up installation and improve image quality. Its P-Iris lens increases image clarity and improves depth of field in any lighting condition, and a mechanical IR cut filter delivers True Day / Night capability. The Smart Compression option reduces storage requirements by up to 70% while maintaining high resolution video allowing you to meet video retention and resolution requirements for less.

This camera uses a new housing design to improve on our IP66-rated seal. Additionally, this camera's new housing and integrated PoE heater provides operation in extreme temperatures as low as -40 °F.

All OpenEye IP cameras are compatible with the OpenEye Web Services platform, allowing multiple users to view high quality images and perform remote setup using a Web browser.

#### FEATURES

- 4MP Maximum Resolution
- 2.7 ~ 12mm Focal Length
- IP66 Rating
- True Day / Night
- True Wide Dynamic Range
- H.264 & H.265 support with Smart Encoding
- MJPG video compression
- 1/2.7" Progressive CMOS Image Sensor
- Adaptive IR Technology
- ONVIF™ Profile S / G / T compliant
- 3-Axis Gimbal Positioning



# SPECIFICATIONS

CAMERA	
<b>Part Number</b>	<b>OE-C7624-AWR REV B</b>
<b>Maximum Resolution</b>	4MP
<b>Image Sensor</b>	1/2.7" Progressive CMOS
<b>Video Compression</b>	H.264 / H.265 / MJPEG
<b>Frame Rate</b>	30FPS @ 4MP - H.264 / H.265
<b>ONVIF</b>	Profile S / G / T compliant
<b>Streaming</b>	Up to 3 simultaneous streams
<b>Browser Support</b>	Internet Explorer (6+) / Chrome / Firefox / Safari
<b>Day / Night</b>	True day / night
<b>Wide Dynamic Range</b>	True WDR
<b>Lens</b>	2.7 ~ 12mm motorized lens
<b>Horizontal Field of View</b>	99° (wide), 31° (tele)
<b>Iris</b>	P-iris F1.6
<b>Min. Illumination @ 30IRE</b>	<b>Color:</b> 0.1 Lux <b>B&amp;W:</b> 0.01 Lux
<b>White Balance</b>	Auto / Manual / ATW / One Push
<b>Auto White Balance Range</b>	2700K ~ 7800K
<b>Backlight Compensation</b>	2500K ~ 10000K
<b>Auto Gain Control</b>	Yes


ENVIRONMENTAL	
<b>IP Rating</b>	IP66 outdoor
<b>Operating Temperature</b>	-40 ~ 131 °F (-40 ~ 55 °C)
<b>Storage Conditions</b>	-4 ~ 158 °F (-20 ~ 70 °C)
<b>UL Listed</b>	Yes

POWER	
<b>Power Consumption</b>	Max 13.68W
<b>Input Voltage</b>	12vDC / 24vAC / PoE
<b>PoE Class</b>	0

PHYSICAL	
<b>IR Range</b>	Up to 130ft
<b>IR LED</b>	Adaptive IR Technology
<b>Analog Output</b>	1.0 Vp-p / 75 Ω, BNC
<b>Audio In / Out</b>	1 Audio In - Stereo phone jack, ø 3.5mm 1 Audio Out - Stereo phone jack, ø 3.5mm
<b>Alarm In / Out</b>	1 Alarm In / 1 Alarm Out
<b>Camera Weight</b>	1.19lb (540g)
<b>Dimensions</b>	<b>W:</b> 5.26 x <b>H:</b> 4.18in (133.8 x 106.3mm)
<b>Housing / Dome Cover</b>	Plastic / metal housing
<b>Country of Origin</b>	Taiwan

# CONNECTIONS


## DONGLE




1	RJ-45	For network and PoE connections		
2	Power (12vDC / 24vAC)	1	12vDC / 24vAC 1	Power connection
		2	GND / 24vAC 2	
3	Audio I/O	Pink	Line Out	Two-way audio transmission
		Green	Line In	
4	BNC	For analog video output		
5	Alarm I/O (4-Pin Terminal Block)	1	Alarm In -	
		2	Alarm In +	
		3	Alarm Out -	
		4	Alarm Out +	

# DIMENSIONS

## FRONT VIEW




## BOTTOM VIEW



## ACCESSORIES




OE-C7624-AWR REV3



# ACCESSORIES



OE-C7624-AWR REV B



OE-CA75APM  
(Pendant Mount Adapter)



OE-CA75PM  
(Pendant Mount)



OE-CA510W  
(7.25" Wall Mount)



OE-CA510WL  
(13.5" Wall Mount)



OE-CA510PA25  
(1.25" Threaded  
Pipe Adapter)



OE-CA510PA50  
(1.5" Threaded  
Pipe Adapter)



OE-CA510P25  
(10" Ceiling Pole  
Mount)



OE-CA510P50  
(20" Ceiling Pole  
Mount)



Kit: OE-CA97CMS  
(Short Arm Corner  
Mount Kit)



Kit: OE-CA97CML  
(Long Arm Corner  
Mount Kit)



Kit: OE-CA97PLMS  
(Short Arm Pole  
Mount Kit)



Kit: OE-CA97PLML  
(Long Arm Pole  
Mount Kit)



Kit: OE-CA97WMS  
(Short Arm Pen-  
dant Mount Kit)



Kit: OE-CA97WML  
(Long Arm Pen-  
dant Mount Kit)