


Product Information Dragonfly Indoor Wi-Fi 6 (802.11ax) Access Point - DAP640

Enterprise WLAN: Wi-Fi 6 access point: Dragonfly Indoor Wi-Fi 6 (802.11ax) Access Point	
Name	Dragonfly Indoor Wi-Fi 6 (802.11ax) Access Point
	
Delivery information	
Availability	available
Product description	
Description	Indoor, dual radio, 5 GHz 802.11ax 4x4:4 and 2.4 GHz 802.11ax 2x2:2, built-in antennas; integrated BLE/Zigbee, scanning and security function
Port type and quantity	<ul style="list-style-type: none"> • 1x 10/100/1000/2500Mbps RJ45 port, Eth0, PoE PD (IEEE 802.3at) • 1x 10/100/1000Mbps RJ45 port, port, Eth1, PoE PD (IEEE 802.3at) • 1 x RJ45 Console Port, • 1 x USB 2.0 Type-A, • 1 x Reset button, • 1 x Kensington security slot
Radio protocol	IEEE 802.11b; 802.11a/g/n/ac; 802.11ax; up to 2.975Gbps (2.402Gbps in 5GHz and 573Mbps in 2.4GHz) data rate
Type	DAP640
Order No.	942999304
Radio technology	
Antenna connector	Built-in 2x2:2 @ 2.4GHz, 4x4:4 @ 5GHz, BLE antenna, Four integrated dual-band downtilt omni-directional antennas for 4x4 MIMO with peak antenna gain of 4.7dBi in 2.4GHz and 4.8dBi in 5GHz.
Frequency band	<ul style="list-style-type: none"> • 2.400 to 2.4835 GHz • 5.150 to 5.250 GHz • 5.250 to 5.350 GHz • 5.470 to 5.725 GHz • 5.725 to 5.850 GHz *available channels: Dependent on configured regulatory domain
Modulation	<ul style="list-style-type: none"> • 802.11b: BPSK, QPSK, CCK • 802.11a/g/n/ac: BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM • 802.11ax: BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM
Additional radio feature	BLE5/Zigbee (802.15.4), scanning and security function
Mechanical construction	
Dimensions (WxDxH)	180mm x 180mm x 36mm
Weight	0.8 kg
Mounting	Wall/ceiling mounting
Power requirement	
Operating voltage	<ul style="list-style-type: none"> • Supports direct DC power and Power over Ethernet (PoE PD) • Direct DC source: 48V DC nominal, +/- 5%
Power consumption	24.8W
Ambient conditions	
Operating temperature	0°C...50°C
Storage/transport temperature	-40°C...70°C
Relative humidity(non-condensing)	5%...95%
Protection class	IP41
Software	
Software features	Auto channel selection; Auto transmit power control; Bandwidth control per SSID; L2 roaming; L3 roaming with DAC software; Band steering; Client smart load balance; NTP server client; Wireless MESH P2P/P2MP
Management	Internal User Database; Zero-touch provisioning (ZTP); System log report; SNMP Trap Notification with DAC software; Floor plan and heat map with DAC software

Enterprise WLAN: Wi-Fi 6 access point: Dragonfly Indoor Wi-Fi 6 (802.11ax) Access Point	
Security	Captive Portal; Radius Client; Wireless QoS; Client sticky avoidance; User behavior tracking; White / black list; ACL; Rogue AP location and containment; Wireless Attack Detection
Authentication & Encryption	<ul style="list-style-type: none"> • 802.11i, Wi-Fi Protected Access 2 (WPA2), WPA, WPA3 (WPA3-Personal, WPA3-Enterprise) • 802.1X • Portal page authentication • Advanced Encryption Standard (AES), Temporal Key Integrity Protocol (TKIP)
Management software	DAC Software, Industrial HiVision
Compliance	
IEEE standard	<ul style="list-style-type: none"> • IEEE 802.11a/b/g/n/ac/ax • IEEE 802.11e WMM • IEEE 802.11h, 802.11i, 802.11e QoS • IEEE 802.11k Radio Resource Management • IEEE 802.11v BSS Transition Management • IEEE 802.11r Fast roaming
Basic standard	CE, FCC, UL
Safety	EN62368-1
Radio	EN 300 328 (2.4 GHz), EN 301 893 (5 GHz), EN 301 489-1, EN 301 489-17
Medical electrical equipment	EN 60601-1-1, EN 60601-1-2
RoHS	RoHS (EU 2015/863) and RoHS(GB/T26572-2011) compliant
Wi-Fi Alliance	Wi-Fi 6 certified, Passpoint
Scope of delivery and accessories	
Scope of delivery	Installation guide, mounting kit (AP-MNT-IN-W)
Accessories to order separately	DC power adapter

RF performance table				
Rate	Receive sensitivity (per chain)		Maximum transmit power (per chain)*	
	2.4 GHz	5 GHz	2.4 GHz	5 GHz
1 Mb/s	-99		18 dBm	
11 Mb/s	-90		18 dBm	
6 Mb/s	-93	-93	17 dBm	18 dBm
54 Mb/s	-77	-77	16 dBm	16 dBm
HT20 (MCS0/8)	-93	-93	17 dBm	17 dBm
HT20 (MCS7/15)	-76	-74	14 dBm	15 dBm
HT40 (MCS0/8)	-91	-90	17 dBm	17 dBm
HT40 (MCS7/15)	-74	-71	14 dBm	15 dBm
VHT20 (MCS0)	-93	-93	17 dBm	17 dBm
VHT20 (MCS8)	-72	-70	14 dBm	15 dBm
VHT40 (MCS0)	-91	-90	17 dBm	17 dBm
VHT40 (MCS9)	-68	-66	14 dBm	15 dBm
VHT80 (MCS0)		-87		17 dBm
VHT80 (MCS9)		-62		15 dBm
HE20 (MCS0)	-94	-93	17 dBm	17 dBm
HE20 (MCS11)	-65	-65	12 dBm	13 dBm
HE40 (MCS0)	-91	-91	17 dBm	17 dBm
HE40 (MCS11)	-62	-62	12 dBm	13 dBm
HE80 (MCS0)		-88		17 dBm
HE80 (MCS11)		-59		13 dBm

*Note: Maximum capability of the hardware provided (excluding antenna gain). Maximum transmit power is limited by local regulatory setting.

For more information please contact:

Belden Singapore - office

151 Lorong Chuan, #05-01
 New Tech Park
 Singapore 556741
 Singapore
 Phone: +65.6879.9800

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.